

# Simulation and Visualization of Carbonation of Concrete based upon New Advanced Numerical Methods Considering Sustainability of Reinforced Concrete Buildings

Toshio Fukushima<sup>1</sup>

<sup>1</sup> Fukushima Institute 2 for Building Environment and Materials (FI2BEM),  
2-chome, 9-18, Otto-Minami, Tsuchiura-shi, Ibaraki-ken, 300-0845 Japan  
Email: fukushima-t-1564@ae.auone-net.jp ; fukutosi@hotmail.com

**Abstract.** Neutralization (Carbonation) of concrete has great influences on the durability of reinforced concrete structures in ordinary atmospheric environment. The progress of carbonation makes the basis of setting service life, maintenance/modernization, and restoration/regeneration of these structures, with the corrosion of reinforcing bars. In considering the sustainability of reinforced concrete buildings and construction, considering the balance among long service life/safety and the environment and economy, we must understand fully the progress of carbonation from the viewpoint of sustainable development goals (SDGs), going back to the starting point. In this paper, the simulation and visualization of carbonation of concrete are done. Based upon mathematical formulation of unsteady state simultaneous diffusion of carbon dioxide in such shell structures as semi-cylindrical and semi-spherical shapes both from outside and inside spaces, computer visualization is carried out on the time-dependent change of concentration of carbon dioxide by advanced numerical analysis making best use of the newest version of mathematical software. By these procedures we can understand the situations of the progress of carbonation corresponding to the various aspects of environmental conditions.

**Keywords:** sustainability, carbonation, shell structures, simultaneous diffusion, numerical analysis

## 1. Introduction

Recently, sustainable development goals (SDGs) are cried for all over the world, involving the United Nations (UN), in order to pursuit for brilliant and hopeful future, by coexistence among nature and environment and human beings, because the global environmental problems such as global warming, depletion of natural resources, and mass generation of waste materials etc. have been threatening the sustainable earth itself. In building field, environment-conscious sustainable buildings and construction are needed by the fusion among science, technologies, and art in the future, to correspond to SDGs involving the climate change [1]. In order to realize sustainable reinforced concrete structures, we consider the balance among the environment,

economy, structural safety/long service life. Neutralization (Carbonation) of concrete has great influences on the durability of reinforced concrete structures in ordinary atmospheric surroundings. With the corrosion of reinforcing steel, the progress of carbonation makes the basis of setting service life [2]-[3], maintenance/modernization, and restore/regeneration of these structures. In considering the sustainability of buildings and construction, we must understand fully the mechanisms of carbonation from the viewpoint of environmental change in external and internal building spaces, going back to the starting point. Looking at the outdoor environment, the concentration of atmospheric CO<sub>2</sub> has been increasing year by year since around 1950 with seasonal fluctuations, and as of 2022, it has already been reported to exceed 410 ppm [4].

Fukushima T. have already reported about the predictive methods of carbonation of concrete considering this trend [5]. In the future, effective reduction, and absorption measures for CO<sub>2</sub> emissions, such as carbon neutrality, will advance, and a certain degree of effect is expected (paradoxical moves to actively use concrete neutralization to absorb CO<sub>2</sub> in the atmosphere seem to be active [6]. However, the concentration of atmosphere CO<sub>2</sub> itself is expected to continue to be on a high trend for the time being. Looking at the indoor environment, in a closed room with insufficient ventilation in winter and summer, when it is compatible with new colonial virus infection, it is necessary to be careful about both air conditioning and ventilation, the indoor CO<sub>2</sub> concentration tends to increase considerably from normal value of 300ppm. For health safety, it is recommended to keep it to 1,000 ppm or less [7]. In order to consider sustainable buildings and cities, and societies, paying special attention to resources circulation and environmental harmony, we should take these trends concerning atmospheric CO<sub>2</sub> into account.

This report deals with the simulation and visualization of the progress of carbonation of concrete in semi-cylindrical and semi-spherical shell by the simultaneous diffusion of carbon dioxide both from outwards and inwards, considering this change of the situations of atmospheric environment by new advanced numerical analysis using the newest mathematical software [10].

## **2. Research Methods**

### **2.1 Mathematical Formulation Simultaneous Diffusion of Carbon Dioxide in Reinforced Concrete Shell**

Mathematical modelling was done for simultaneous diffusion of CO<sub>2</sub> in semi-cylindrical and semi-spherical reinforced concrete shells. Fundamental partial second-order diffusion are formulated as fundamental equations with the initial and boundary conditions:

### **2.2 Numerical Analysis**


For numerical solution, program of NDSolve of Mathematical software of Mathematica<sup>10)</sup> is used. As the effective diffusion coefficient, the value of 3.1536[mm<sup>2</sup>/year<sup>-1</sup>] is used, which corresponds to the one of ordinary Portland cement

concrete with 45% water-cement ratio. But, for the convenience of visualization, a hundredfold value is set. As the value of pseudo-first order carbonation rate constant,  $0.01[\text{year}^{-1}]$  is used. Numerical method in cases of diffusion with pseudo-first order carbonation reaction is shown as follows:


$$\text{NDSolve}\left[\left\{D[u(r,t),r,r] + \frac{D[u(r,t),r]}{r} == \frac{D[u(r,t),t]}{0.31536} - \frac{0.01}{0.31536} u(r,t), u(r,0) == 1000 \text{Exp}[-100000000(50000 - r)(r - 4960)], u(r,t), \{r, 0.0001, 40\}, \{t, 0, 200\}\right\}\right] \quad (1)$$

### 3. Research Results


Figures 1a), 1b), 2a), 2b) show the results of simulation and visualization.




**Fig.1a). 3DPlot of the Progress of Carbonation in in Semi-cylindrical Shell**



**Fig.1b). Plot of the Progress of Carbonation in Semi-cylindrical Shell**



**Fig.2a). 3DPlot of the Progress of Carbonation in Semi-spherical Shell**



**Fig.2b). Plot of the Progress of Carbonation in Semi-spherical shell**

## 4. Summary and Conclusion

Paying special attention to the change of concentration of external and internal atmospheric carbon dioxide, simulation and visualization were done by making best use of the newest numerical analysis. The progress of carbonation of concrete by simultaneous diffusion of carbon dioxide both from inwards and outwards in semi-cylindrical and semi-spherical reinforced concrete shell was shown as time-dependent visual images. These procedures of simulation and visualization is useful to well understand the carbonation of concrete in various aspects.

## References

1. Architectural Institute of Japan: "Standard Specifications and Explanation for Building Construction: Reinforced Concrete Work" (JASS5 (2018 edition))
2. Hamada M., Neutralization (Carbonation) of Concrete and Corrosion of Reinforcing Steel, in: Proceedings of the 5th International Symposium on Chemistry of Cement, held on 7-11 October, 1968, in Tokyo, Japan Cement Association, Vo.1.3, pp. 349-369(1968)
3. Fukushima T.: Service life of Reinforced Concrete Buildings-Based upon Neutralization and Corrosion of Reinforcing steel-, Gihodo Press, 142 pp. (1990) (in Japanese)
4. Japan Meteorological Agency Homepage: Changes in Concentrations over Time of Atmospheric Carbon Dioxide:  
[https://ds.data.jma.go.jp/ghg/kanshi/ghgp/co2\\_trend.html](https://ds.data.jma.go.jp/ghg/kanshi/ghgp/co2_trend.html), last accessed 2021/11/21.
5. Special Issue on "Concrete Technology Contributing to Carbon Neutrality", Concrete Engineering, Vol. 59, No.9 (September 2021)
6. Architectural Institute of Japan Homepage: Urgent Messages of Meeting of Chair persons of Architectural Institute of Japan, and Japan Society of Air Conditioning and Sanitary Engineering: Ventilation in the Control of New Coronavirus Infections:  
<https://www.aij.or.jp/jpn/databox/2020/200323.pdf>, last accessed 2022/03/20
7. Architectural Institute of Japan Homepage: SDGs Declaration:  
<https://www.aij.or.jp/jpn/databox/2021/AIJ-SDGs.pdf>, last accessed 2022/03/20
8. Fukushima, T: Predicative Methods on the Progress of Neutralization (Carbonation) of Concrete by Unsteady State Dynamic Analysis Considering the Influence of Tendency of Increase in Concentration of Atmospheric Carbon Dioxide, In. Proceedings of the Second CANMET / ACI International Conference on Durability of Concrete, held on August1-4, in 1991, in Montreal, Canada, edited by V. M. Malhotra, ACI Publication SP-126, Vol.1, American Concrete Institute, Vol. 1, pp.545-564(1991)
9. Fukushima T., Analytical Method of Neutralization of Concrete by Carbon Dioxide (in the Case of Cylindrical Shape), Japanese Patent: No. 6468517, Japan Patent Agency` (2020`)
10. Wolfram Research Inc.: Mathematica Ver.13. (2022)